



scheda tecnica

technical data

41211

Miscelatore incasso con doccetta igienica
Built in mixer with shut-off handshower

CR - NI - TN - TB - LC

- Monocomando comando a leva
- Cartuccia D25 con dischi ceramici LT25-G25
- Leva zama
- Rosone scorrevole
- Parte incasso da installare prima di piastrellare
- Senza scarico
- Installazione con dima di riferimento
- Tappo per prova di tenuta dell'impianto idrico
- Attacchi all'impianto idrico G1/2"
- Attacco flessibile doccia G1/2
- Flessibile ottone con gomma atossica
- Doccetta ottone monogetto
- Garanzia 5 anni

- Mixer with lever
- 25 diameter cartridge with ceramic discs LT25-G25
- Zamak lever
- Sliding rosette
- Concealed part to be installed prior to tiling
- Without pop-up waste
- Installation with plaster reference
- Plug for water supply leakage test
- Water supply connections G1/2"
- Flex hose shower connection G1/2
- Brass flex hose with atossic rubber
- Brass handshower single spray
- 5 years guarantee

- Portata 9 litri/min (3 bar)

- Flow rate 9 liters/min (3bar)

- Riferimenti normative:
- EN 817 - EN32
- Rivestimento superficiale Ni-Cr a norma EN 248

- Reference standards:
- EN 817 - EN32
- Resistance surface coating Ni-Cr in according EN 248

- Presenti parti da incassare prima di concludere i lavori di muratura

- Item includes parts to be installed prior to tiling

LA TORRE srl
28045 Invorio - (NO)
Via Altovergante, 33
ITALY



Tel. +39 0322 255391 r.a.
Fax +39 0322 255442
www.rubinetteria-latorre.it
info@rubinetteria-latorre.it



rev0_08.2018



Con riserva di modifiche - Subject to change



41211 ita_eng_metric_rev0